

ONDUVILLA 3D PPHR Tiles

Uses	ONDUVILLA 3D PPHR tiles is a new range of corrugated bitumen tiles designed for giving the roofing a pleasant aspect by reminding the traditional clay tiles look + a 3D effect.																											
Description	<p>MONOLAYER corrugated tiles made of organic fibres saturated with high grade bitumen. An exclusive 3-tone coating system makes each tile unique, naturally looking as dark strip at the top of the tile provides a 3D effect.</p> <p>Matches with ETA 10-/0018 requirements, technical approval from EOTA.</p>																											
Fixing guide	<p>Refer to ONDUVILLA BOOK or to other appropriate ONDUVILLA leaflet.</p> <p>Span mandatory: 32 cm (overlap = 8 cm insured by 2 safety strips lines).</p> <p>Minimum pitch : 15 % (full board), 30% (purlins).</p>																											
Dimensions and mass	<table border="1"> <thead> <tr> <th></th> <th>Unit</th> <th>Target value and [tolerances]</th> </tr> </thead> <tbody> <tr> <td>Length</td> <td>mm</td> <td>400 [- 0 + 20]</td> </tr> <tr> <td>Width</td> <td>mm</td> <td>1070 [- 20 + 20]</td> </tr> <tr> <td>Thickness</td> <td>mm</td> <td>2.9 [-0.3 + 0.3]</td> </tr> <tr> <td>Corrugation depth</td> <td>mm</td> <td>38 [-2 + 2]</td> </tr> <tr> <td>Corrugation pitch</td> <td>mm</td> <td>95 [-2 + 2]</td> </tr> <tr> <td>Flat part</td> <td>mm</td> <td>95 [-2 + 2]</td> </tr> <tr> <td>Profile</td> <td></td> <td>6 corrugations + 5 flat parts</td> </tr> <tr> <td>Weight</td> <td>kg</td> <td>1.27 [-0.1 + 0.1]</td> </tr> </tbody> </table>		Unit	Target value and [tolerances]	Length	mm	400 [- 0 + 20]	Width	mm	1070 [- 20 + 20]	Thickness	mm	2.9 [-0.3 + 0.3]	Corrugation depth	mm	38 [-2 + 2]	Corrugation pitch	mm	95 [-2 + 2]	Flat part	mm	95 [-2 + 2]	Profile		6 corrugations + 5 flat parts	Weight	kg	1.27 [-0.1 + 0.1]
	Unit	Target value and [tolerances]																										
Length	mm	400 [- 0 + 20]																										
Width	mm	1070 [- 20 + 20]																										
Thickness	mm	2.9 [-0.3 + 0.3]																										
Corrugation depth	mm	38 [-2 + 2]																										
Corrugation pitch	mm	95 [-2 + 2]																										
Flat part	mm	95 [-2 + 2]																										
Profile		6 corrugations + 5 flat parts																										
Weight	kg	1.27 [-0.1 + 0.1]																										
Technical characteristics	<table border="1"> <thead> <tr> <th>Nominal Characteristic</th> <th>Unit</th> <th>Value</th> <th>Method</th> </tr> </thead> <tbody> <tr> <td>Water tightness</td> <td></td> <td>Watertight</td> <td>EN 534</td> </tr> <tr> <td>Resistance to bursting (compression breaking)</td> <td>bars (daN/cm²)</td> <td>> 16</td> <td>NFQ 03 053</td> </tr> </tbody> </table>	Nominal Characteristic	Unit	Value	Method	Water tightness		Watertight	EN 534	Resistance to bursting (compression breaking)	bars (daN/cm ²)	> 16	NFQ 03 053															
Nominal Characteristic	Unit	Value	Method																									
Water tightness		Watertight	EN 534																									
Resistance to bursting (compression breaking)	bars (daN/cm ²)	> 16	NFQ 03 053																									
Range and packaging	<p>Exists in 3D shaded brown, 3D shaded red and 3D shaded green and black.</p> <p>Packaging: 7 (DIY) or 15 (PRO) tiles per bundle.</p> <p>57 (DIY) or 60 (PRO) bundles per pallet.</p>																											